







Field display devices allow users to view and collect data, as well as download programs, at the field site.

| | Display/Keyboard Description | Temperature Range |
|---|---|---|
| Mesa 2 MS2-100 Rugged Tablet, Standard North American Model Popular  | 17.78 cm (7 in.) display and touch sensor | <ul style="list-style-type: none"> ➤ -30° to +70°C (storage) ➤ -20° to +50°C (operating) |
| CR1000KD Keyboard/Display for CR1000(X), CR800, or CR6 Popular  | 8 lines x 21 characters (64 x 1238 pixels) display and 16-character keyboard | <ul style="list-style-type: none"> -20° to +50°C (operating) |
| CD100 Mountable Display with Keypad  | <ul style="list-style-type: none"> ➤ Vacuum fluorescent ➤ 8 lines x 21 characters (64 x 128 pixels) display and 16-character keyboard | <ul style="list-style-type: none"> ➤ -45° to +85°C (operating) ➤ -60° to +85°C (1 h) transit ➤ -50° to +85°C (storage) |
| CD295 DataView II Display  | 2 lines x 32 characters display and 2- button keyboard | <ul style="list-style-type: none"> ➤ -25° to +70°C (asleep) ➤ -20° to +55°C (operating) |

For comprehensive details, visit: www.campbellsci.com/field-displays 