



Rugged, Accurate, Versatile

Can be used in a variety of applications

Overview

The 107 is a rugged, accurate probe that measures temperature of air, soil, or water from -35° to +50°C. It easily interfaces with most Campbell Scientific data loggers and can be used in a variety of applications.

The 107 consists of a thermistor encapsulated in an epoxy-filled aluminum housing. The housing protects the thermistor, allowing you to bury the probe in soil or submerge it in water.

Benefits and Features

- › Versatile product—measures air, soil, or water temperature
- › Easy to install or remove
- › Durable
- › Compatible with AM16/32-series multiplexers, allowing measurement of multiple sensors

Specifications

Sensor Description	BetaTherm 100K6A11A Thermistor
Tolerance	±0.2°C (over 0° to 50°C range)
Temperature Measurement Range	-35° to +50°C
Temperature Survival Range	-50° to +100°C
Steinhart-Hart Equation Error	≤±0.01°C over measurement range (CRBasic data loggers only)
Polynomial Linearization Error	Typically < ±0.5°C over measurement range (Edlog data loggers only)
Time Constant in Air	30 to 60 s (in a wind speed of 5 m s ⁻¹)

Maximum Submergence	15 m (50 ft)
Probe Diameter	0.76 cm (0.3 in.)
Probe Length	10.4 cm (4.1 in.)
Maximum Cable Length	› 305 m (1000 ft) is typical and requires no programming changes. › 762 m (2500 ft) requires programming changes. (Refer to section 8.4 of the 107 manual for assistance.)
Weight	136 g (5 oz) with (3.05 m) 10 ft cable

For comprehensive details, visit: www.campbellsci.com/107 