



## IEC 61400-12 Class 1 Anemometer

Ideal for wind-energy  
applications

### Overview

The A100LK is an anemometer suitable for your general meteorology applications and wind-energy surveys. Its low power consumption and wide power-supply range make it popular for remote locations with no access to ac power, and its pulse/frequency signal is ideal for use with Campbell

Scientific data loggers. The sensor is constructed from anodized aluminum alloys, stainless steel, and weather-resistant plastics for long life. It is used as part of our WMS100 wind-monitoring system.

### Benefits and Features

- ▶ IEC Class 1 performance
- ▶ Low power consumption
- ▶ High rate of pulses per revolution produced makes it suitable for wind-surveying applications where turbulence is estimated
- ▶ Bearings protected from the entry of moisture droplets and dust, resulting in an instrument suitable for permanent exposure to the weather

### Detailed Description

Rotation of the A100LK's three-cup rotor is electronically converted to pulse output signals proportional to wind speed. The A100LK produces a higher rate of pulses per revolution (up

to 13) compared to relay-based sensors, making it suitable for wind surveying where turbulence needs to be estimated.

### Specifications

Sensor	3-cup anemometer
Measurement Description	Wind speed
Signal Type/Output	Electronic pulse

Range	0 to 77 ms <sup>-1</sup>
Threshold	0.15 ms <sup>-1</sup> (starting speed 0.2 ms <sup>-1</sup> , stopping speed 0.1 ms <sup>-1</sup> )

Maximum Speed	77.22 ms <sup>-1</sup>
Accuracy	1% ±0.1 ms <sup>-1</sup>
Distance Constant	2.3 m ±10%
Calibration Data	Supplied for anemometer and rotor at one test speed to an accuracy of ±1% at +15°C. (12 Vdc supply and an analog output load of 1 MΩ)
Operating Temperature Range	-30° to +70°C
Rotor	15.2 cm (6 in.) diameter three-cup rotor

Supply Voltage	6.5 to 28 Vdc
Current Consumption	2 mA maximum 1.6 mA typical (no output load)
Power-up Time	5 s
Surge Protection	Vector PC3L2 anti-surge module fitted
Housing Diameter	5.5 cm (2.2 in.)
Height	19.5 cm (7.68 in.)
Weight	490 g (17.3 oz) including 3 m (10 ft) cable

For comprehensive details, visit: [www.campbellsci.com/a100k](http://www.campbellsci.com/a100k) 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | [www.campbellsci.com](http://www.campbellsci.com)  
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA