





## Overview

With an A21REL-12, your Campbell Scientific data logger can control up to four external ac or dc devices. This relay driver

## **Detailed Description**

The A21REL-12's internal relays are single-pole double-throw. This relay driver may be powered by the data logger power has four internal relays.

supply or a separate 12 Vdc battery.

## **Specifications**

Function	Allows a data logger to control up to four external ac or dc devices.
Number of Channels	4
Contact Ratings	<ul> <li>0.3 A (at 120 Vac)</li> <li>1 A (at 20 Vdc)</li> </ul>
Coil Current	13 mA/relay

Relays	dual single-pole, double-throw relays
Operating Temperature	-25° to +50°C
Operating Voltage	12 Vdc
Dimensions	14.0 x 6.9 x 3.0 cm (5.5 x 2.7 x 1.2 in.)
Weight	227 g (8 oz)

G CAMPBELL<sup>®</sup> SCIENTIFIC For comprehensive details, visit: www.campbellsci.com/a21rel-12

Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | www.campbellsci.com AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | <mark>USA</mark>