





## Overview

The CM300 is a 58 cm (23 in.), stainless-steel, 1.5 in. IPS vertical pole. It is designed for mounting sensors, enclosures, or other instruments, and is an ideal mount for remote sensors such as a tipping bucket rain gage or net radiometer. Our CS700, TB4, and 385 rain gages are typically mounted to the CM300 via the CM240 leveling base. This mounting pole can be embedded

directly into a concrete foundation or used with a pedestal kit. (See Ordering Info on the web page.)

**Note:** Grounding connections from the mounting pole to the system's main tripod/tower or to the ground are important to help protect the system and measurements. The parts to establish these grounding connections are not included with the mounting pole.

## **Specifications**

Material	Stainless-steel pipe 1.5 IPS
Outer Diameter	4.8 cm (1.9 in.)
Length	58 cm (23 in.)
Weight	3.2 kg (7 lb)
Short Leg Kit	
Material	Stainless-steel tubing 1.5 OD
Leg Length	58 cm (23 in.)
Pedestal Height and Radius	<ul> <li>Note: The pedestal height is foot/ground to bottom of mast vertical distance, and it is adjustable to the following:</li> <li>11 cm (4 in.) height and a 66 cm (26 in.) radius for Hole F</li> <li>33 cm (13 in.) height and a 55 cm (22 in.) radius for Hole C</li> </ul>

<ul> <li>36 cm (14 in.) height and a 51 cm (20 in.) radius for Hole B</li> <li>41 cm (16 in.) height and a 46 cm (18 in.) radius for Hole A</li> <li>27 cm (11 in.) height and a 59 cm (23 in.) radius for Hole D</li> <li>22 cm (9 in.) height and a 63 cm (25 in.) radius for Hole E</li> </ul>
Stainless-steel tubing 1.5 OD
99 cm (39 in )

Leg Length	99 cm (39 in.)
Pedestal Height and Radius	<ul> <li>Note: The pedestal height is foot/ground to bottom of mast vertical distance, and it is adjustable to the following:</li> <li>20 cm (8 in.) height and a 105 cm (41 in.) radius for Hole F</li> </ul>

For comprehensive details, visit: www.campbellsci.com/cm300

Long Leg Kit

Material

- 41 cm (16 in.) height and a 97 cm (38 in.) radius for Hole E
- 50 cm (20 in.) height and a 91 cm (36 in.) radius for Hole D
- 59 cm (23 in.) height and a 85 cm (34 in.) radius for Hole C
- 66 cm (26 in.) height and a 77 cm (30 in.) radius for Hole B

73 cm (29 in.) height and a 69 cm (27 in.) radius for Hole A

## J-bolt Kit

J-bolt Material	Stainless steel
J-bolt Size	1/2-13 in. x 12 in.

For comprehensive details, visit: www.campbellsci.com/cm300



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | www.campbellsci.com AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA