




CRS451

Stainless-Steel Stand-Alone Pressure Transducer



Self-Contained Memory

Easy to use software, reliable hardware

Overview

The CRS451 consists of a water-level and water-temperature sensor that has its own time clock and memory to store the collected data, in a compact stainless-steel case. This frees users to place the sensor in remote sites and let it collect data for long periods. The sensor can then be retrieved, connected to a PC via a micro-USB port, and the data transferred to the

PC. HydroSci software is included and elegantly supports test setup, data retrieval, and data display. Long battery life and rugged construction mean you can trust the CRS451 to collect important data. Low cost and ease of use make it a good choice in a variety of applications. The CRS456 is the same as this, but with a titanium case.

Benefits and Features

- › Sensors and data-collection features in one instrument case
- › Rugged stainless-steel case protects piezoresistive sensor
- › Quality construction ensures product reliability
- › Fully temperature-compensated
- › Fast scan rate
- › Large data-storage capacity
- › Long battery life
- › Easy-to-use software

Detailed Description

The CRS451 has several pressure range options. The CRS451 is unvented; therefore it is monitoring sealed gage pressure. For maximum accuracy, the data should be corrected for barometric pressure.

HydroSci software is available for [download](#). This software simplifies the process of configuring the CRS451. Users can configure the CRS451 to monitor surface water, ground water, or a standard pump test.

HydroSci software will also compensate the measurements for barometric pressure using an additional CS451 or a CS456 as a reference sensor, or using a barometric pressure sensor from a nearby weather station.

HydroSci software will display the data in tabular or graphical formats.

Specifications

Venting	Unvented
Measurement Time	< 1.0 s
Output Options	micro USB
Internal Data Collection Memory	4 MB
Logging/Scanning Modes	Standard, Delta, Wave, Logarithmic
Resolution	0.0035% FS
Dry Storage Temperature Range	-10° to +80°C WARNING: Sensor could be damaged if encased in frozen ice.
Operating Temperature Range	0° to 60°C WARNING: Sensor could be damaged if encased in frozen ice.
Overpressure	2 x pressure range
Power Requirements	Internal user-replaceable lithium battery
Water-Level Accuracy	±0.1% full-scale-range TEB Includes the combined errors due to nonlinearity, hysteresis, nonrepeatability, and thermal effects over the compensated temperature range, per ISA S51.1.
Battery Life	5 years (when logging interval is once per hour)

Body Material	316L stainless steel
Temperature Accuracy	±0.2°C
Ingress Protection	Exceeds IP68
Diameter	2.22 cm (0.875 in.)
Length	22.23 cm (8.75 in.)
Weight	230 g (0.51 lb)

Power Consumption

Quiescent	< 80 µA
Measurement/Communication	4 mA (1 s measurement)

Measurement Ranges at Fresh Water Depths

0 to 5.1 m (16.7 ft)	› 0 to 50 kPa › 0 to 7.25 psi
0 to 10.2 m (33.4 ft)	› 0 to 14.5 psi › 0 to 100 kPa
0 to 20.4 m (67 ft)	› 0 to 200 kPa › 0 to 29 psi
0 to 50.9 m (167 ft)	› 0 to 72.5 psi › 0 to 500 kPa
0 to 102 m (334.5 ft)	› 0 to 145 psi › 0 to 1000 kPa

For comprehensive details, visit: www.campbellsci.com/crs451 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | www.campbellsci.com
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA

© 2020 Campbell Scientific, Inc. | 10/06/2020