



CS526-L

Digital ISFET pH Sensor



More Durable, Safer

Elimination of glass bulb for
longer time in field

Overview

The CS526 isolated pH probe makes reliable, accurate pH measurements in aqueous solutions. It can be submersed or

inserted into tanks, pipelines, and open channels. This probe has a serial, TTL output that represents a 2 to 12 pH range.

Benefits and Features

- › Innovative ISFET pH-sensing element
- › Easily cleaned
- › More rugged than the traditional glass electrode pH probes
- › Each sensor individually tested
- › Designed and manufactured under stringent quality control conditions in an ISO 9001 environment
- › CE compliant

Detailed Description

The CS526 uses SENTRON's high-tech, ion sensitive field effect transistor (ISFET) semiconductor as its pH-sensitive element, and includes a silver/silver chloride– potassium chloride reference system. The CS526's design allows it to be suitable for a variety of liquid pH-monitoring applications. The electronics are safely embedded in a durable PEEK body. Elimination of the glass bulb removes the possibility of broken glass, making the CS526 more rugged and safer to use.

Note: Campbell Scientific warranty does not cover a clogged reference diaphragm or improperly cleaned or maintained ISFET chip. (See the Maintenance section in the instruction manual for more information.)

This sensor requires the 5 V output on the data logger to be powered..

Specifications

pH Range	2 to 12
Power Requirements	5 Vdc

Current Consumption	15 mA (maximum)
Accuracy	±0.2 pH (over 10° to 40°C)

Operating Temperature Range	10° to 40°C
Output	<ul style="list-style-type: none"> › no parity › 1 stop bit › 8 data bits › 2400 bps › Serial TTL logic
24 h Drift	< 0.15 pH (after 15 min. soak in pH 7 at 25°C)
Allowed Water Pressure	0 to 700 kPa (0 to 101.5 psi)

Cable Type	Three-twisted pair, 24 AWG cable with Santoprene jacket
Sensor Material	Polyetheretherketone (PEEK)
Maximum Cable Length	100 m (328 ft)
Diameter	16 mm (0.63 in.)
Length	102 mm (4 in.)
Weight	318 g (11.2 oz) with 3.05 m (10 ft) cable

For comprehensive details, visit: www.campbellsci.com/cs526 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | www.campbellsci.com
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | THAILAND | SOUTH AFRICA | SPAIN | UK | [USA](#)