



Temperature-Compensated Output

Overview

The SR50AT-L is an acoustic distance sensor that measures the elapsed time between emission and return of an ultrasonic pulse. This measurement can be used to determine snow depth. The SR50AT-L includes an external temperature sensor

and outputs a temperature-corrected distance reading, eliminating the need for further post-processing.

Note: Campbell Scientific recommends model [SR50AT-316SS-L](#) for marine environments.

Benefits and Features

- › Integrated temperature probe for providing temperature correction of measurements
- › Non-contact method for determining snow depth
- › Wide operating temperature range
- › Rugged enough for harsh environments
- › User-selectable options for output
- › Uses a multiple echo processing algorithm to help ensure measurement reliability
- › Compatible with most Campbell Scientific data loggers

Detailed Description

The SR50AT is an identical unit to the SR50A with the addition of an external temperature sensor. The temperature sensor requires a six-plate radiation shield. The SR50AT will output a temperature-corrected distance reading, eliminating the need for further post-processing, as well as a separate temperature reading.

The SR50AT was designed to meet the stringent requirements of measuring snow depths and uses a multiple echo

processing algorithm to help ensure measurement reliability. The SR50AT is compatible with all current Campbell Scientific data loggers, as well as many other data acquisition systems. An air temperature measurement is required to correct for variations of the speed of sound in air. Either the SR50AT or an existing on-site air temperature sensor can be used. The SR50AT is available with a heater option for locations where rime ice is a problem.

Specifications

Measurement Time	< 1.0 s
Output Options	SDI-12 version 1.3, RS-232, RS-485 (output options selected by configuring internal jumpers)
Baud Rates	1200 to 38400 bps (RS-232, RS-485 modes)
Power Requirements	9 to 18 Vdc (typically powered by data logger's 12 Vdc power supply)
Measurement Range	0.5 to 10 m (1.6 to 32.8 ft)
Beam Acceptance Angle	~30°
Resolution	0.25 mm (0.01 in.)
Accuracy	±1 cm (0.4 in.) or 0.4% of distance to target (whichever is greatest).
Operating Temperature Range	-45° to +50°C
Compliance	CE compliant
Temperature Accuracy	<ul style="list-style-type: none"> › ±0.2° (at 0° to 50°C) › ±0.75° (at -45° to 0°C)
Cable Type	4 conductor, 2-twisted pair, 22 AWG, Santoprene

Diameter	7.6 cm (3 in.)
Length	10.1 cm (4 in.)
Weight	375 g (13.2 oz) without cable
Cable Weight	250 g (8.2 oz) for a 4.57-m (15-ft) cable

Power Consumption

Active	250 mA (typical)
Quiescent SDI-12 Mode	< 1.0 mA The quiescent current draw is less than 1.25 mA if the BAUD rate is 9600 BAUD or less
RS-232/RS-485 Mode	< 2.0 mA

Maximum Cable Length

<i>-NOTE-</i>	<i>Cable lengths greater than 60 m require a heavier gage wire if the power supply drops below 11 Vdc.</i>
SDI-12	60 m (200 ft)
RS-232	60 m (200 ft) 9600 BAUD or less
RS-485	300 m (984 ft)

For comprehensive details, visit: www.campbellsci.com/sr50at-l 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | www.campbellsci.com
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA

© 2020 Campbell Scientific, Inc. | 12/23/2020