



Evaluate Live- Load Stresses

Overview

The ST350, manufactured by Bridge Diagnostics, Inc., is a strain transducer used to evaluate live-load stresses on structures such as bridges, buildings, cranes, and amusement park rides. It

is prewired to connect directly with our data loggers, and is ideal for structural monitoring data acquisition systems.

Benefits and Features

- Improved signal-to-noise ratio means higher-resolution measurements
- **>** Rugged enough for harsh environments
- **)** Pay for themselves with just a few uses

- **)** Compatible with most Campbell Scientific data loggers
- **)** Quick installation with minimal preparation
- **)** Efficient, reliable, and highly accurate

Detailed Description

The ST350 uses Wheatstone bridge circuitry, which converts small changes in resistance to an output voltage that our data loggers can measure. Its construction avoids the tedious and time-consuming effort required when using foil strain gages.

This allows the ST350 to be installed within minutes on steel, concrete, timber, and FRP members.

Specifications

Accuracy	±2% (individually calibrated to NIST standards)	Circuit
Force Required for 1000 με ~76 N (17 lb)		
Strain Range	±2000 με	Cable
Sensitivity	~500 με/mV/V	

Circuit	Full Wheatstone bridge with 4 active 350 Ω foil gages, 4-wire hookup
Cable	BDI RC-187 (22 gage, two individually shielded pairs with drain: 15 ft length standard)

Material Aluminum Dimensions 11.1 x 3.2 x 1.3 cm (4.375 x 1.25 x 0.5 in.) Weight 85 g (3 oz)