



## Overview

The UTHD is a durable instrument tower that can be used in a variety of monitoring applications. The UTHD is an aluminum, corrosion-resistant instrumentation tower with four tower height options and high wind load ratings at user-selectable tower heights.

Data logger and power supply enclosures, solar panel(s), crossams, and other meteorological instrumentation mount to the tower legs. An optional Sun Tracker Mount provides a sturdy platform at the top of the UTHD for permanent deployment of a precision Sun Tracker for advanced solar resource assessment and power performance monitoring. This optional mount works with Sun Trackers such as Kipp & Zonen (Solys2) or EKO Instruments (STR-21G or STR-22G).

## Benefits and Features

- ▶ User-selectable height options
- ▶ Sturdy, long-term instrument mount with robust mounting option for industry standard Sun Trackers
- ▶ Higher wind load rating than the UT10, UT20, or UT30 towers
- ▶ Wider legs to enable mounting standard Campbell Scientific mounting equipment
- ▶ Top portion ends without traditional triangle connections and a mast

## Specifications

Material	Hardened drawn 6063-T832 aluminum
Required Concrete Pad Dimensions	91 x 91 x 122 cm (36 x 36 x 48 in.) for B18 Concrete Mounting Base
	Concrete pad requirements assume heavy soil; light, shifting, or sandy soils require a larger concrete pad.

-NOTE-

*Allowable wind gust specifications were calculated with the following: one enclosure, two crossarms mounted with two CM210 crossarm mounts each (one crossarm with a wind monitor, the other crossarm with two pyranometers), and B-18 anchors used to secure the stand to the ground. In addition, the*

*concrete footing has a 91.4 cm (36 in.) length, a 91.4 cm (36 in.) width, and a 122 cm (48 in.) depth.*

---

Allowable Wind Gusts at 220.98 cm (87 in.)	239.9 kph (149 mph)
--	---------------------

---

Allowable Wind Gusts at 175.26 cm (69 in.)	260.7 kph (162 mph)
--	---------------------

---

Allowable Wind Gusts at 129.54 cm (51 in.)	280.0 kph (174 mph)
--	---------------------

---

Allowable Wind Gusts at 96.52 cm (38 in.)	Not rated
---	-----------

---

Leg Spacing	43.2 cm (17.0 in.)
-------------	--------------------

---

Height	User-selectable
--------	-----------------

---

Weight	4.16 kg (9.18 lb)
--------	-------------------

---

For comprehensive details, visit: [www.campbellsci.com/uthd](http://www.campbellsci.com/uthd) 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | [www.campbellsci.com](http://www.campbellsci.com)  
AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA