App. Note Code: 3SM-F Revision: 4



CF Card Information

CompactFlash (CF) cards provide a relatively inexpensive, off-the-shelf means of retrieving data from many of our CRBasic dataloggers or expanding the onboard datalogger memory. The datalogger's memory can be expanded to 16 GB or more with the use of these cards. Table 1 lists the compatibility between dataloggers and CF cards.

Table 1. CRBasic Dataloggers and CF Cards			
Datalogger	CF Card Compatible	Required Device/Adapter	
CR200(X)	no	N/A	
CR800/850	no	N/A	
CR6	typically uses a microSD card instead of a CF card		
CR1000	yes	CFM100 or NL115 connected to peripheral port	
CR3000	yes	CFM100 or NL115 connected to peripheral port	
CR5000	yes	CF1 adapter connected to onboard PCMCIA card slot	
CR9000X	yes	CF1 adapter connected to onboard PCMCIA card slot	

CF cards use NAND (Not AND) Flash (non-volatile) memory which has the following characteristics: high density, low cost per bit, sequential access, scalable, and a single standard. There are two types of NAND Flash memory: Single-Level Cell (SLC) and Multi-Level Cell (MLC). SLC NAND Flash sometimes called Binary Flash, store one bit of data per memory cell and has two states: erased (1) or programmed (0). MLC NAND Flash store two bits of data per memory cell and has four states: erased (11), two thirds (10), one third (01), or programmed (00)¹. At first glance, the MLC cards seem more desirable, because each cell can hold more information. However, as summarized in Table 2, the increased data storage comes at a price, mainly speed.

Table 2. SLC and MLC Performance Characteristics			
	SLC	MLC	
Voltage	3.3 V / 1.8 V	3.3 V	
Page Size / Block Size	2 kB / 128 kB	512 B / 32 kB or 2 kB / 256 kB	
Access Time (maximum)	25 μs	70 μs	
Page Program Time	250 μs	1.2 ms	
Partial Programming	Yes	No	
Endurance	100,000	10,000	
Write Data Rate	8 MB/s	1.5 MB/s	

There is a notable performance difference between the two types of NAND Flash memory. In a performance study by Samsung Electronics², Samsung found that SLC outperformed MLC, offering greater durability, running 300% faster in write mode, and 43% faster in read mode. While MLC Flash increases the overall density of data storage, which therefore decreases cost; it does so at the expense of data reliability, performance and memory management. Furthermore, MLC technology is more prone to failure, data corruption, or incorrect reading due to memory cell degradation from the additional energy required during operations².

There are two types of CF cards available today: Industrial Grade and Standard or Commercial Grade. Industrial Grade CF cards are held to a higher standard; specifically they operate over a wider temperature range, offer better vibration and shock resistance, and have faster read/write times than their commercial counterparts (Table 3). The Industrial Grade cards more closely match the operating envelope of the dataloggers and for this reason we recommend you always use extended temperature tested, Industrial Grade CF cards with a datalogger.

Table 3. Comparison of Industrial and Commercial Grade Cards			
Specification	Industrial Grade	Commercial Grade	
Operating Temperature	−40 to 85 °C	0 to 70 °C	
Vibration Proofing	30 Gs	15 Gs	
Shock Resistance	2000 Gs	1000 Gs	
MTBF @ 25 °C	>4,000,000 hours	>1,000,000 hours	
Type of NAND Flash Memory	SLC	MLC typically but some SLC	

All Campbell Scientific products are electrostatic discharge (ESD) tested to ensure that in the event of a static discharge neither the equipment nor the data is damaged or lost and that the equipment resumes operation. Campbell Scientific ESD tested several brands of cards, only the FMJ and Swissbit cards passed this testing and operate properly with the datalogger. Campbell Scientific recommends that only cards that have passed out testing be used with Campbell Scientific CRBasic dataloggers. It is not necessary to purchase the cards directly from Campbell Scientific, as long as the manufacturer and model number match Table 4. FMJ cards are distributed by Falcon Electronics (www.falconelec.com/contact/).

Table 4. FMJ, Swissbit, and Campbell Scientific CF model numbers				
Size (GB)	FMJ Model	Swissbit Model	Campbell Scientific Model	
1	CFV-1GB-TSI-3522	not available	not available	
2	CFV-2GB-TSI-3522	SFCF2048H1BO2TO-I-M0-543-SMA	CFMC2G	
4	CFV-4GB-TSI-3522	SFCF4096H1BO2TO-I-D1-543-SMA	not available	
8	CFV-8GB-TSI-3524	SFCF8192H1BO2TO-I-Q1-543-SMA	not available	
16	CFV-16GB-TSI-3524	SFCF16GBH1BO4TO-I-Q1-543-SMA	CMC16G	
32	CFV-32GB-TSI-3524	SFCF32GBH1BO4TO-I-NC-543-SMA	not available	

References

1. "Implementing MLC NAND Flash for Cost-Effective, High-Capacity Memory', written by Raz Dan and Rochelle Singer, September 2003, 91-SR-014-02-8L, REV 1.1,

http://dataioinfo.com/pdf/NAND/MSystems/Implementing MLC NAND Flash.pdf

2. "Advantages of SLC NAND Flash Memory", http://memory.com.my/SLC%20VS%20MLC.html

Campbell Scientific Companies

Campbell Scientific, Inc. (CSI)

815 West 1800 North Logan, Utah 84321 UNITED STATES

www.campbellsci.com • info@campbellsci.com

Campbell Scientific Africa Pty. Ltd. (CSAf)

PO Box 2450 Somerset West 7129 SOUTH AFRICA

www.csafrica.co.za • cleroux@csafrica.co.za

Campbell Scientific Australia Pty. Ltd. (CSA)

PO Box 8108 Garbutt Post Shop QLD 4814 AUSTRALIA

www.campbellsci.com.au • info@campbellsci.com.au

Campbell Scientific (Beijing) Co., Ltd.

8B16, Floor 8 Tower B, Hanwei Plaza 7 Guanghua Road Chaoyang, Beijing 100004 P.R. CHINA

www.campbellsci.com • info@campbellsci.com.cn

Campbell Scientific do Brasil Ltda. (CSB)

Rua Apinagés, nbr. 2018 — Perdizes CEP: 01258-00 — São Paulo — SP BRASIL

www.campbellsci.com.br • vendas@campbellsci.com.br

Campbell Scientific Canada Corp. (CSC)

14532 – 131 Avenue NW Edmonton AB T5L 4X4 CANADA

www.campbellsci.ca • dataloggers@campbellsci.ca

Campbell Scientific Centro Caribe S.A. (CSCC)

300 N Cementerio, Edificio Breller Santo Domingo, Heredia 40305 COSTA RICA

www.campbellsci.cc • info@campbellsci.cc

Campbell Scientific Ltd. (CSL)

Campbell Park
80 Hathern Road
Shepshed, Loughborough LE12 9GX
UNITED KINGDOM
www.campbellsci.co.uk • sales@campbellsci.co.uk

Campbell Scientific Ltd. (CSL France)

3 Avenue de la Division Leclerc 92160 ANTONY FRANCE

www.campbellsci.fr • info@campbellsci.fr

Campbell Scientific Ltd. (CSL Germany)

Fahrenheitstraße 13 28359 Bremen GERMANY

www.campbellsci.de • info@campbellsci.de

Campbell Scientific Spain, S. L. (CSL Spain)

Avda. Pompeu Fabra 7-9, local 1 08024 Barcelona SPAIN

www.campbellsci.es • info@campbellsci.es

Please visit www.campbellsci.com to obtain contact information for your local US or international representative.